

## AUTOLUBE TX 2000

### APPLICATION

A UNIQUE FORMULATION DESIGNED TO MEET THE REQUIREMENTS OF PASSENGER CAR AND LIGHT TRUCK PETROL AND DIESEL ENGINES WHERE API SF/CC PERFORMANCE IS REQUIRED.

### PERFORMANCE LEVEL (API SF/CC)

MEETS OR EXCEEDS:

- MB 225.0
- US MIL-L-21260 AND MIL-L-2104B
- ADE Pg 3
- CCMC G2-D1
- SABS 1361

### BENEFITS

- THE SPECIALLY DESIGNED COMBINATION OF DETERGENT AND DISPERSANT ADDITIVES MAINTAINS POWER OUTPUT BY CONTROLLING PISTON AND RING DEPOSITS.

TYPICAL PHYSICAL CHARACTERISTICS	SAE 30	SAE 40
DENSITY @ 20°C KG/L	0.892	0.895
VISCOSITY cST @ 40°C	95	145
VISCOSITY Cst @ 100°C	9.3 - 12.5	12.5 - 16.3
VISCOSITY INDEX	106	99
POUR POINT, °C (MAX)	-18	-15
FLASH POINT °C (MIN)	240	258
TBN mg KOH / G	6	6
SULPHATED ASH, m%	0.7	0.7
ZINC, m%	0.12	0.12

RE: 2001/11/01