

AUTOLUBE MULTISERVICE GREASE EP2

MULTIPURPOSE EP GREASE, LITHIUM THICKENER, EP ADDITIVES AND RUST AND OXIDATION INHIBITORS.

APPLICATION

■ AUTOMOTIVE ■ CONSTRUCTION ■ EARTHMOVING, QUARRYING AND MINING
■ AGRICULTURAL EQUIPMENT ■ WHEEL BEARINGS ■ CHASSIS GREASE POINT LUBRICATION ■ INDUSTRIAL ROLLING ELEMENT BEARINGS

USABLE TEMPERATURE RANGE IN CONTINUOUS SERVICE IS:

NLGI 2: -30 TO 130°C

MAXIMUM TEMPERATURE FOR SHORT TERM EXPOSURE IS 175°C.

BENEFITS

- EFFECTIVE EP ADDITIVE PROTECTS AGAINST COMPONENT WEAR UNDER HIGH LOAD CONDITIONS. EFFECTIVE RUST AND CORROSION INHIBITORS PROTECTS METAL SURFACES IN WET OPERATING CONDITIONS.
- MULTIPURPOSE CAPABILITY ALLOWS USE IN A WIDE RANGE OF AUTOMOTIVE AND INDUSTRIAL APPLICATIONS, REDUCING THE NUMBER OF DIFFERENT GREASES REQUIRED AND ELIMINATING PRODUCT MISAPPLICATION.

TYPICAL PHYSICAL CHARACTERISTICS	NLGI GRADE 2
DROPPING POINT, °C	195
OIL VISCOSITY, mm ² /s @ 40°C	208
mm ² /s @ 100°C	18.2
PENETRATION, WORKED @ 25°C	280
THICKENER (LITHIUM), m%	7.5
TIMKEN OK LOAD, KG	18

RE: 01/05/2011