

# **AUTOLUBE MULTIPURPOSE GEAR OIL (GL - 4)**

HIGH PERFORMANCE, MULTIPURPOSE MILD EXTREME PRESSURE GEAR LUBRICANT.

## **APPLICATION**

■ MANUAL TRANSMISSIONS, TRANSAXLES, PLANETARY HUB & OTHER SPUR GEAR AXLES WHICH SPECIFICALLY REQUIRE MILD EP GEAR OILS MEETING API GL-4

## **PERFORMANCE LEVEL (API GL4)**

MEETS OR EXCEEDS:

- MULTIPURPOSE EP OR HYPOID GEAR OIL
- MIL-L-2105
- MB 235.5
- MAN 34 ML

## **BENEFITS**

- HIGH PERFORMANCE, EP ADDITIVE SYSTEM CONTROLS TRANSMISSION GEAR TOOTH WEAR, EXCELLENT LOAD CARRYING CAPACITY TO PROTECT GEAR EQUIPMENT AGAINST SURFACE STRESS UNDER HEAVILY LOADED CONDITIONS

<b>TYPICAL PHYSICAL CHARACTERISTICS</b>	<b>80W90</b>	<b>90</b>
DENSITY @ 20°C KG/L	0.893	0.9
VISCOSITY cST @ 40°C	146	192
VISCOSITY cST @ 100°C	13.5 - 24	13.5 - 24
VISCOSITY INDEX	106	102
POUR POINT °C (MAX)	-33	-15
FLASH POINT °C (MIN)	220	222
SULFUR, WT %	0.4	0.4
PHOSPHORUS, WT %	0.045	0.045
NITROGEN, WT%	0.03	0.03
CHLORINE, PPM	<0.5	<0.5

RE: 2001/11/2001