

AUTOLUBE MULTIPURPOSE GEAR OIL

HIGH PERFORMANCE, MULTIPURPOSE EXTREME PRESSURE GEAR LUBRICANT.

APPLICATION

■ SERVICE: DIFFS, MANUAL TRANSMISSIONS & OTHER GEAR CASES OF AUTOMOTIVE EQUIPMENT

PERFORMANCE LEVEL (API GL5)

MEETS OR EXCEEDS:

- MUTIPURPOSE EP OR HYPOID GEAR OIL
- MIL-L-2105D
- MACK GO-H

BENEFITS

- HIGH PERFORMANCE, SULFUR-PHOSPHORUS EP ADDITIVE SYSTEM PROVIDES EXCELLENT LOAD CARRYING CAPACITY TO PROTECT GEAR EQUIPMENT AGAINST SURFACE STRESS UNDER HEAVILY LOADED CONDITIONS

TYPICAL PHYSICAL CHARACTERISTICS	80W90	90	85W140
DENSITY @ 20°C KG/L	0.893	0.9	0.909
VISCOSITY cST @ 40°C	134	192	296
VISCOSITY cST @ 100°C	13.5 - 24	13.5 - 24	24.0 - 41
VISCOSITY INDEX	106	102	108
POUR POINT °C (MAX)	-33	-15	-21
FLASH POINT °C (MIN)	200	200	212
SULFUR, WT %	0.27	0.27	0.27
PHOSPHORUS, WT %	0.09	0.09	0.09
NITROGEN, WT%	0.06	0.06	0.06
CHLORINE, PPM	<10	<10	<10

RE: 2001/11/2001