

AUTOLUBE SUPER TRACTOR OIL UNIVERSAL

HIGH PERFORMANCE, MULTIPURPOSE EXTREME PRESSURE GEAR LUBRICANT.

APPLICATION

■ SERVICE: DIFFS, MANUAL TRANSMISSIONS & OTHER GEAR CASES OF AUTOMOTIVE EQUIPMENT

PERFORMANCE LEVEL (API CF4/GL5)

MEETS OR EXCEEDS:

- GL 5 LOW SPEED / HIGH TORQUE
- CCMC D4
- JOHN DEERE J27
- REDUCED WET BRAKE NOISE
- MASSEY FERGUSON M1139
- FORD M2C-159B
- FORD 134-D

BENEFITS

- UNIQUE MULTI APPLICATION ADDITIVE PACKAGE ENABLES USE IN ENGINES, TRANSMISSIONS, FINAL DRIVES AND HYDRAULIC SYSTEMS, AVOIDING COSTLY EQUIPMENT FAILURE DUE TO MISAPPLICATION
- SPECIAL FRICTION MODIFIER COMPONENT ALLOWS SMOOTH ACTION OF WET BRAKES AND POWER TAKE-OFF CLUTCHES, MINIMIZING CHATTER, STICK SLIP AND SQUAWK

TYPICAL PHYSICAL CHARACTERISTICS	SAE 20W40
DENSITY @ 20°C KG/L	0.892
VISCOSITY cST @ 40°C	134
VISCOSITY cST @ 100°C	15
VISCOSITY INDEX	114
POUR POINT °C (MAX)	-24
FLASH POINT °C (MIN)	240
TBN mg KOH/g	10.7
ZINC, m%	0.14

RE:2001/11/01